



Declaration of performance according to Annex III of Regulation [EU] No 305/2011 (Construction Products Regulation BAUPVO)

No. 18_Hg

1. Unique identification code of the product type:
See annex to the declaration of performance
2. Type, batch or serial number or other mark identifying the construction product in accordance with Article 11 (4):
Bidets
3. Intended use or uses of the construction product as intended by the manufacturer in accordance with the applicable harmonised technical specification:
Personal hygiene
4. Name, registered trade name or registered trade mark and contact address of the manufacturer in accordance with Article 11 (5):
**Hansgrohe SE
Austraße 5-9
77761 Schiltach
Germany
info@hansgrohe.com**
5. If applicable, name and contact address of the authorised representative entrusted with the tasks pursuant to Article 12 (2):
**Hansgrohe Ltd.
Unit 2
Edgehill Drive
Tournament Fields
Warwick, CV346XQ**
6. System or systems for assessment and verification of constancy of performance of the construction product in accordance with Annex V:
System 4
7. In the case of the declaration of performance concerning a construction product covered by a harmonised standard:
Establishment of the product-type and factory production control by the manufacturer

8. Declared performance:

| Main Features | Performance | Harmonised technical specification |
|-------------------------------------|------------------|------------------------------------|
| Overflow drainage value (OF) | Technical class* | EN14528:2007 |
| Cleanability (CA) | Passed / NPD* | |

AXOR**hansgrohe**

Declaration of performance according to Annex III of Regulation [EU] No 305/2011 (Construction Products Regulation BAUPVO)

No. 18_Hg

| | | |
|--|---------------|--|
| Static load capacity (LR) | Passed / NPD* | |
| Durability (DA) | Passed / NPD* | |
| * The specific performance of the essential characteristics is indicated by the designation code, as mentioned in the Appendix. If no performance has been determined for an essential characteristic, this is indicated by "NPD". | | |

9. The performance of the product in accordance with points 1 and 2 shall be declared performance in accordance with point 8, in an uninstalled condition. A performance description for the installation must be provided by the responsible person/company/qualified personnel. The manufacturer alone is responsible for drawing up this declaration of performance in accordance with Number 4.

Signed for and on behalf of the manufacturer by:

DocuSigned by:

 2994474224C14F8...
 Jay Phillips
 Managing Director
 Hansgrohe Ltd.
 Warwick, 03.12.2024

DocuSigned by:

 72E96101F2D244E...
 i.A. Nicole Michels
 Group Compliance Officer
 Hansgrohe SE
 Schiltach, 03.12.2024



Declaration of performance according to Annex III of Regulation [EU] No 305/2011 (Construction Products Regulation BAUPVO)

No. 18_Hg

Annex:

| Materialnummer | Bezeichnung | CA | LR | DA | OF |
|----------------|---|----|----|----|------|
| 6027845x | EluPura S WH Bidet 540 w. TPH w. Overflow, white | ✓ | ✓ | ✓ | CL25 |
| 6116945x | EluPura S WH Bidet 540 w. TPH w. Overflow, SMC white | ✓ | ✓ | ✓ | CL25 |
| 6204345x | EluPura S WH Bidet 540 w. TPH w. Overflow, HYE white | ✓ | ✓ | ✓ | CL25 |
| 6028145x | EluPura Original S WH Bidet 540 w. TPH w. Overflow, white | ✓ | ✓ | ✓ | CL25 |
| 6117145x | EluPura Original S WH Bidet 540 w. TPH w. Overflow, SMC white | ✓ | ✓ | ✓ | CL25 |
| 6204545x | EluPura Original S WH Bidet 540 w. TPH w. Overflow, HYE white | ✓ | ✓ | ✓ | CL25 |
| 6028445x | EluPura Original Q WH Bidet 540 w. TPH w. Overflow, white | ✓ | ✓ | ✓ | CL25 |
| 6117245x | EluPura Original Q WH Bidet 540 w. TPH w. Overflow, SMC white | ✓ | ✓ | ✓ | CL25 |
| 6204645x | EluPura Original Q WH Bidet 540 w. TPH w. Overflow, HYE white | ✓ | ✓ | ✓ | CL25 |
| 6028045x | EluPura Q WH Bidet 540 w. TPH w. Overflow, white | ✓ | ✓ | ✓ | CL25 |
| 6117045x | EluPura Q WH Bidet 540 w. TPH w. Overflow, SMC white | ✓ | ✓ | ✓ | CL25 |
| 6204445x | EluPura Q WH Bidet 540 w. TPH w. Overflow, HYE white | ✓ | ✓ | ✓ | CL25 |

* The ending -x is replaced by 0, 2 or 5 for different retail packaging