

hansgrohe

EN Instructions for use / assembly instructions

DE Gebrauchsanleitung / Montageanleitung

2







English



Safety Notes

- crushing and cutting injuries.
- and body cleaning purposes.
- ⚠ The hot and cold supplies must be of equal. pressures.

Installation Instructions

- Prior to installation, inspect the product for transport damages. After it has been installed, no transport or surface damage will be honoured.
- The pipes and the fixture must be installed, flushed and tested as per the applicable standards.
- · The plumbing codes applicable in the respective countries must be observed.
- 71025009: The drain valve must only be used as intended. It is not allowed to attach other objects to the drain valve, for example a semi-pedestal.
- The mixer can not used together with a continuous flow water heater.

Technical Data

Operating pressure: max. 1 MPa 0,1 - 0,5 MPa Recommended operating pressure: Test pressure: 1.6 MPa

(1 MPa = 10 bar = 147 PSI)

Hot water temperature: max. 70°C 65°C Recommended hot water temp.: Thermal disinfection: max. 70°C / 4 min The product is exclusively designed for drinking water!

Symbol description



Do not use silicone containing acetic acid!

Adjustment (see page 6)

To adjust the hot water limiter. Using a hot water limiter in combination with a continuous flow water heater is not recommended.



Dimensions (see page 8)



Flow diagram (see page 8)



Spare parts (see page 10)

Special accessories (order as an extra)



- special tool #58085000 (see page 4)
- Installation putty (see page 5)



Cleaning (see page 12)

Operation (see page 7)

Hansgrohe recommends not to use as drinking water the first half liter of water drawn in the morning or after a prolonged period of non-use.



Deutsch

Sicherheitshinweise

- ⚠ Bei der Montage m
 üssen zur Vermeidung von Quetsch- und Schnittverletzungen Handschuhe getragen werden.
- △ Das Produkt darf nur zu Bade-, Hygiene- und Körperreinigungszwecken eingesetzt werden.
- △ Große Druckunterschiede zwischen den Kalt- und Warmwasseranschlüssen müssen ausgeglichen werden.

Montagehinweise

- Vor der Montage muss das Produkt auf Transportschäden untersucht werden. Nach dem Einbau werden keine Transport- oder Oberflächenschäden anerkannt.
- Die Leitungen und die Armatur m

 üssen nach den gültigen Normen montiert, gespült und geprüft
- Die in den Ländern jeweils gültigen Installationsrichtlinien sind einzuhalten
- 71025009: Das Ablaufventil darf nur zum bestimmungsgemäßen Gebrauch verwendet werden. Das Befestigen von anderen Gegenständen z. B. einer Halbsäule an dem Ablaufventil ist nicht zulässia.
- Die Armatur kann nicht in Verbindung mit einem Durchlauferhitzer verwendet werden.

Technische Daten

Betriebsdruck: max. 1 MPa Empfohlener Betriebsdruck: 0,1 - 0,5 MPa Prüfdruck: 1.6 MPa (1 MPa = 10 bar = 147 PSI)

Heißwassertemperatur: max. 70°C Empfohlene Heißwassertemperatur: 65°C Thermische Desinfektion: max. 70°C / 4 min

Das Produkt ist ausschließlich für Trinkwasser konzipiert!

Symbolerklärung



Kein essigsäurehaltiges Silikon verwenden!



Justierung (siehe Seite 6)

Einstellen der Warmwasserbegrenzung. In Verbindung mit Durchlauferhitzern ist eine Warmwassersperre nicht zu empfehlen.



Maße (siehe Seite 8)

Durchflussdiagramm (siehe Seite 8)



Serviceteile (siehe Seite 10)

Sonderzubehör

(nicht im Lieferumfang enthalten)



 Montageschlüssel #58085000 (siehe Seite 4)



• Installationskitt (siehe Seite 5)



Reinigung (siehe Seite 12)





Bedienung (siehe Seite 7)


Hansgrohe empfiehlt, morgens oder nach längeren Staanationszeiten den ersten halben Liter nicht als Trinkwasser zu verwenden.












































































close / schließen



cold / kalt





hot/warm



Novus 230


max. 40 -Ø32 **←** G1/2








Novus 230






Focus 230 31972009 / 31973009






Focus 230

31972009




Focus 230

31973009






Novus 230







Focus 230 31972009 / 31973009





EN Cleaning recommendation / Warranty / Contact

Reinigungsempfehlung / Garantie / Kontakt



cleaning-recommendation



www.hansgrohe.com/ cleaning-recommendation



www.hansgrohe.com/ cleaning-recommendation



www.hansgrohe.com/ cleaning-recommendation

